

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
17 July 2003 (17.07.2003)

PCT

(10) International Publication Number
WO 03/057446 A1

(51) International Patent Classification⁷: B29C 45/14

(21) International Application Number: PCT/NL03/00016

(22) International Filing Date: 10 January 2003 (10.01.2003)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1019729 11 January 2002 (11.01.2002) NL

(71) Applicant (for all designated States except US): CORUS
TECHNOLOGY BV [NL/NL]; P.O. Box 10000, NL-1970
CA IJmuiden (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): VAN DER AA,


Hendrikus, Christianus, Engelbertus [NL/NL]; Du-
venvoordestraat 45 zw, NL-2013 AC Haarlem (NL).
VERDIER, Anthony, Stephan [NL/NL]; Driedistel
42, NL-1954 Le Heemskerk (NL). DE WOLF, Hugo,
Gerrit, Jan [NL/NL]; Van Zeggelenplein 19, NL-2032
KA Haarlem (NL).

(74) Agent: KRUIT, Jan; Corus Technolgy BV, P.O. Box
10000, NL-1970 CA IJmuiden (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: METHOD AND DEVICE FOR PRODUCING A COMPOSITE PRODUCT, AND COMPOSITE PRODUCT PRO-
DUCED THEREWITH



(57) Abstract: A method for producing a composite product comprising a plastic body and a covering layer formed from a metal blank (5) which at least over part of its surface is stuck to the plastic body, wherein - the metal blank (5) is placed in a die, which die comprises a blank holder (24), a mandrel (22) which can move with respect to the blank holder (24), and a support die (21), - the die is closed, so that the support die (21) and the mandrel (22) are located on either side of the metal blank (5), and the metal blank is supported in the vicinity of its edge with the aid of the blank holder (24), - a liquid plastic is injected into the die, the liquid plastic being brought into contact with the preformed metal blank (5), - the liquid plastic being converted into a solid plastic body which is stuck to the preformed metal blank (5) in order to produce the composite product, - the composite product is removed from the die.